PAT-NO:

JP362158757A

DOCUMENT-IDENTIFIER: JP 62158757 A

TITLE:

KEY BOARD MATERIAL

PUBN-DATE:

July 14, 1987

INVENTOR-INFORMATION:

NAME

OSHIMA, YUTAKA

ASSIGNEE-INFORMATION:

NAME

COUNTRY

NIPPON GAKKI SEIZO KK

N/A

APPL-NO:

JP61001207

APPL-DATE:

January 7, 1986

INT-CL (IPC): C08L101/00, C08K003/00, C08L077/00,

G10C003/12

## ABSTRACT:

PURPOSE: To obtain a keyboard material which has waterabsorbing properties,

is good to the touch and allows production to be efficiently conducted, by

blending a thermoplastic resin with a water-soluble polyamide resin.

CONSTITUTION: A keyboard material is obtd. by blending 100pts.wt.

thermoplastic resin with 10∼50pts.wt. water-soluble polyamide resin and

not more than 150pts.wt. inorg. filler. As the thermoplastic resin, polyamide resins are preferred from the viewpoint of compatibility with the

water-soluble polyamide. Further, an inorg. filler can be blended therewith.

The inorg. filler is effective in retaining the rigidity of the keyboard material and increasing the thermal conductivity. However, it is not always

necessary to blend the filler. The keyboard material has advantages in that

(1) it has proper water-absorbing properties so that perspiration on fingers

can be absorbed during performance and mistouching due to slipping caused by

perspiration can be prevented; (2) it has touch, body and a coefficient of

friction comparable with natural ivory; and (3) it can be produced simply and

rapidly by a synthetic resin molding method and the productivity is high.

COPYRIGHT: (C)1987,JPO&Japio